

**POLYFLOR CAMARO STONE & DESIGN PUR**

- Camaro - collection of versatile vinyl floor products
- Stone, slate and marble effect floorcovering designs
- Coordinating grouting, marquetry and feature strips are readily available to blend, shape or accentuate design ideas

**SPECIFICATION**



2.0mm

0.3mm

36 @ 305 x 305mm = 3.34m<sup>2</sup>  
 18 @ 610 x 305mm = 3.34m<sup>2</sup>  
 16 @ 457 x 457mm = 3.34m<sup>2</sup>

3600g/m<sup>2</sup>



**GENERAL PERFORMANCE**

EN 649  
 EN ISO 10582



**REACTION TO FIRE**  
 EN 13501-1 Class Bfl-S1



**ABRASION RESISTANCE**  
 EN 649 Group T  
 EN ISO 10582 Type 1



**SLIP RESISTANCE**  
 EN 13893 Class DS (dry condition)\*  
 DIN 51130 R10  
 AS/NZS 4586 R10



For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges



**INDENTATION - RESIDUAL**  
 EN 433 <0.05mm  
 EN ISO 24343-1 ≤ 0.05mm



**DIMENSIONAL STABILITY**  
 EN 434 <0.1%  
 EN ISO 23999 ≤ 0.1% max.



**CASTOR CHAIR (continuous use)**  
 EN 425 / ISO 4918 Suitable



**THERMAL CONDUCTIVITY**  
 Suitable for underfloor heating heating Max 27°C



**LIGHT FASTNESS**  
 ISO 105-B02 (Method 3) ≥6



**RESPONSIBLE SOURCING**  
 BES 6001 Very good  
 SA 8000 Approved factory



**ELECTRICAL BEHAVIOUR (body voltage)**  
 EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



**VOC EMISSIONS**  
 Indoor Air Comfort GOLD - Eurofins certified product  
 AgBB - Very low emissions  
 FloorScore - Certified product



**ENVIRONMENTALLY PREFERABLE FLOORING**  
 Polyflor Camaro PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. Camaro PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



Camaro PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.



**APPLICATIONS**  
 Camaro PUR is suitable for use in any domestic situation and moderate commercial areas such as offices, hotels and boutiques.



**CAMARO**  
 FLOORING COLLECTION

**STONE & DESIGN**



**PERFORMANCE AND PROPERTIES**



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

