


TECHNICAL DATA SHEET
FLOORPAN
 WINGS

8 MM - CLASS 33 - AC5

THICKNESS	mm	8	EN 13329+A2
WIDTH	mm	197	EN 13329+A2
LENGHT	mm	1205	EN 13329+A2
SURFACE		Sky	
EUROPEAN STANDARD	-		EN 13329
PACKAGE DETAILS			
PIECE	8 piece / 1 package		
Area (m ²)	1,9 m ²		
Weight (kg)	14 kg		
PALLET DETAILS			
PACKAGE	56 package / 1 pallet		
Area (m ²)	106,4 m ²		
Weight (kg)	810 kg		
CLASS	-	33	EN 13329+A2
ABRASION RESISTANCE	-	AC5	EN 13329+A2
THICKNESS SWELLING	%	≤15	ISO 24336
SURFACE SWELLING (Assembled joint)	Qualitative Rating	Rating (1-5)	ISO 4760 (NALFA 72h)
	Quantitative Rating	mm	
RESISTANCE TO IMPACT	SMALL BALL	N	EN 13329+A2
	LARGE BALL	mm	
BODY VOLTAGE IN WALKING TEST (Antistatic Floor Covering)	kV	BV=0,9	EN 1815:2016-09
WARRANTY DOMESTIC / COMMERCIAL	Years	25/15	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438-2_5
SURFACE SOUNDNESS	N/mm ²	≥1.25	EN 13329+A2
LOCK STRENGTH	LENGHT	kN/m	ISO 24334
	WIDTH	kN/m	
EFFECT OF CASTOR CHAIR ^a	25.000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A2
HEIGHT DIFFERENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A2
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C _s S1	EN 9239-1
FORMALDEHYDE RELEASE	mg/m ² h	≤3,5 (E1)	EN 12460-3
SLIP RESISTANCE	Class	-	EN 13893:2003
IMPACT SOUND REDUCTION	dB	15	EN ISO 10140-3
THERMAL RESISTANCE	(m ² K)/W	0,0614	EN 12667:2001



Our products can also be produced with FSC® and CARB certification upon request.